# **Permissions**

We have a very granular permission system that allows you permission up to individual objects (e.g. an audience) and fields (e.g. the name of an audience).

#### Contents on this page

- POST /<object\_type>/grant
  - Description
  - Endpoint
  - Method
  - Parameters
- POST /permission/index
  - Description
  - Endpoint
  - Method
  - Parameters
  - Example of configuration

# POST /<object\_type>/grant

## **Description**

Grant permission on object. Note: This service is embedded in the individual object endpoints, but is currently not yet available on all object types. Please reach out to tech@flxone.com if you need additional support.

### **Endpoint**

/<object\_type>/grant

#### Method

POST

#### **Parameters**

Name	Туре	Required	Description	
id	int	Υ	The ID of the object you want grant permissions to	
user	string	Y *	Comma separated list of user IDs you want to give access	
user_group	int	Y *	Comma separated list of user group IDs you want to give access	

<sup>\*</sup> You need to provide at least one user or one user group. You can also combined these in one call.

# POST /permission/index

## Description

Add custom permission (advanced usage)

### **Endpoint**

/permission/index

### Method

POST

### **Parameters**

Name	Туре	Required	Description
name	string	Υ	The name
configuration	string	Υ	JSON configuration
user_group_id	int	N	User Group Id
description	string	N	The description

## **Example of configuration**

```
[
        "effect": "allow",
        "resource_type": "*",
        "resource_path": "*",
        "methods": [
             " * "
        ],
        "actions": [
             11 * 11
        ],
        "resources": [
             "entity:tracking/id:1",
   "entity:tracking/id:2"
        ]
    }
]
```